INFORMATION

INFORMATION REPORT

CENTRAL INTELLIGENCE AGENCY

This material contains information affecting the National Defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C. Secs. 793 and 794, the transmission or revelation of which in any manner to an unauthorized person is prohibited by law.

C-C-W-F-I-D-R-X-I-I-I-A-L NOFORN

COUNTRY Bullgaria **REPORT** Svilengrad Bailroad Yards (Repair FountigATE DISTR. 10 December 1959 50X1-HUM NO. PAGES 3 REFERENCES RD 50X1-HUM DATE OF INFO. PLACE & DATE ACQ SOURCE EVALUATIONS ARE DEFINITIVE. APPRAISAL OF CONTENT IS TENTATIVE.

Size and Equipment

50X1-HUM

- 1. Svilengred railroad yards contain approximately 15 Times of track and 30 rollers for temporary line repairs. There are 300 to 900 neters of track for manduvering cars; one locomotive with five or six cars can be re-directed. Tracks numbers 2 through 5 are operated electrically by remote 750X1-HUM control; tracks numbers 7 and 8 are used to store freight core 50X1-HUM and can hold approximately 150 freight cars. The average number of cars in the yards at one time is 50.
- 2. There is not a large amount of railroad equipment in the yards. The only locomotive permanently assigned to the pards is used for moving railroad care. It is an old Valsa locomotive of German manufacture with three ordes and 60 to 65-ton conacity.
- 3. Water from a well is purped by electricity or steam power to the concrete water tank of 50-ton capacity at one end of the yard. Hear the platform at the station there is a balance of h0 to h5-ton capacity for weighing railroad cars. Approximately 75 to 30 tons of coal is stored in the yards; it comes from the Dimitrovo coal mines and is coal of 6,500 to 5,000 calories. The coal is transported by three crames, one of which is situated in the engine house.

Repair Work

X ARMY

X NAVY (Note: Washington distribution indicated by "X"; Field distribution by "#".)

4. The entire house, which can hold four locomotives, has two tunnels for repairs and eleaning; two tracks run through it. There are two winches, one of 15-ton and the other of 10-ton capacity. There is no repair workshop. Locomotives are sent to Dimitrov rad for lubrication and minor repairs and to Plovdiv for major repairs.

> C-O-H-P-I-D-E-H-T-1-A-L HOFORM

INFORMATION REPORT INFORMATION

50X1-HUM

